

PRODUCT DATA SHEET

TFT BLITZFIRE PORTABLE MONITOR

XXC-32-BJ1: BlitzFire Portable Monitor + Max-Force Automatic Nozzle Package - 65 mm BSPF Swivel Rocker Inlet, 65 mm BSPM Rigid Outlet, Storage Bracket

The BlitzFire® is an adaptable, high-performance portable water monitor, ideal for fire crews facing limited manpower or challenging firefighting conditions. Delivering up to 500 GPM (2000 LPM) with full control over water flow and attack angles, the BlitzFire® can be used in either attended or unattended mode. Its exclusive safety shutoff valve ensures operation under the safest possible conditions, while its compatibility with various nozzles and foam systems adds versatility to its use. Whether you need to adjust your stream angle to reach high or low locations, the BlitzFire® is a reliable, efficient solution that maximizes fireground capabilities.

FEATURES

- Flow Rate: Flows up to 500 GPM (2000 LPM) for powerful water delivery
- Safety Shutoff Valve: Automatically shuts off water in case of unintentional monitor movement
- Adjustable Attack Angles: 10° -46° for standard models; up to 86° for high elevation units
- Slide Valve Control: Provides complete control with six distinct detent positions for precise stream management
- Foam Compatibility: Compatible with various foam systems for enhanced fire suppression
- Optional Oscillation: Covers a range of 20°, 30°, or 40° without manual adjustment for effective cooling and exposure protection
- Carbide-Tipped Legs: Offers enhanced stability on uneven terrain
- Compact Storage: Easily mounted or stored in apparatus compartments for rapid deployment

XXC-32-BJ1 INCLUDES:

XX132A – BlitzFire® Monitor

- 2.5" (65mm) BSPF Swivel Rocker Inlet
- 2.5" (65mm) BSPM Outlet
- Horizontal Movement: 20° left and right of center
- Vertical Movement: 10° -46° above horizontal
- Turbulence-free slide valve
- Safety Shut-Off Valve

MD22A – Max-Force Nozzle

- 100/55 PSI (7/4bar) Dual-Pressure Nozzle
- Flow Capacity: 100-500 GPM (400-2000 LPM)
- Stream: Straight Stream to a 120° wide fog

XX-B – Storage Bracket



SPECIFICATIONS

Package	Y
Colour	Blue
Brand	BlitzFire®
Bundle	Monitor Package
Monitor Type	Ground Attack
Bundle Nozzle Type	Automatic
Bundle Nozzle Brand	Max-Force
Monitor Supply Size	65 mm
Monitor Supply Type	BSP Female
Monitor Supply Style	Rocker
Monitor Supply Swivel	Swivel
Monitor Horizontal Range	±20°
Monitor Vertical Range	10° – 46°
Monitor Control	Manual
Monitor Supply Inlets	Single
Monitor Outlet Size	65 mm
Monitor Outlet Type	BSP Male
Monitor Outlet Style	Male Threads
Monitor Outlet Swivel	Rigid
Max Flow Rate (LPM)	2000 LPM
Bundle Stream Straightener	Integrated
Bundle Storage/Mount Bracket	Included
Monitor Valve Type	Slide Valve
Safety Features	Safety Shutoff & Tie Down Strap